

# TG-X 930

Condenser Microphone



## FEATURES

- High-quality vocals microphone
- Very constant cardioid polar pattern
- Compensated close-talking effect
- Wire mesh basket without foam
- Shock mounted microphone transducer and electronics
- Available in black (TG-X 930) or velour nickel (TG-X 930 Ni)



TG-X 930



TG-X 930 Ni

## APPLICATIONS

The TG-X 930 is a high-quality vocals microphone with compensated close-talking effect, which is ideal for sophisticated live or studio applications. No foam is used in the multilayer wire mesh basket, which provides optimum protection against popping and wind noise, and is easy to clean. This feature also results in a very constant cardioid polar pattern with excellent feedback rejection. To avoid handling noise, the electronics and microphone transducer are shock mounted.

The TG-X 930 provides a 3-pin male XLR connector to connect to any microphone input with phantom power supply (44 - 52 V). The TG-X 930 is supplied with the MKV 8 microphone clamp for stands with 3/8" thread.

## VERSIONS

- |             |  |
|-------------|--|
| TG-X 930    | Condenser microphone, black, cardioid, with MKV 8 microphone clamp with 3/8" internal thread for shaft $\varnothing$ 22 - 32 mm. . . . . Order # 495.220 |
| TG-X 930 Ni | same as above, but velour nickel . . . . . Order # 495.212   |

## OPTIONAL ACCESSORIES

### Microphone clamp

- |          |  |
|----------|--|
| EA 19/25 | Elastic suspension<br>19 - 25 mm, incl. MKV 11-<br>microphone clamp. . . . . Order # 407.194 |
| MKV 6    | Microphone clip for<br>shaft $\varnothing$ 19 - 32 mm. . . . . Order # 407.208               |

### Microphone cables

- |           |  |
|-----------|--|
| BMC 05 FM | Standard microphone cable<br>XLR-XLR, 5 m long. . . . . Order # 434.787  |
| BMC 10 FM | Standard microphone cable<br>XLR-XLR, 10 m long. . . . . Order # 434.795 |

### Stands

- |         |   |
|---------|---|
| GST 400 | Microphone stand, 3/8",<br>height 0.90 - 1.65 m,<br>with G 400 boom. . . . . Order # 421.294                |
| GST 500 | Microphone stand, 3/8",<br>height 0.85 - 1.60 m,<br>with telescopic<br>G 500 boom . . . . . Order # 406.252 |
| ST 400  | Microphone stand, 3/8",<br>height 0.90 - 1.65 m . . . . . Order # 421.286                                   |
| ST 500  | Microphone stand, 3/8",<br>height 0.85 - 1.60 m . . . . . Order # 406.643                                   |

### Germany

beyerdynamic GmbH & Co. KG  
Theresienstr. 8 · 74072 Heilbronn – Germany  
Tel. +49 (0)7131 / 617-0 · Fax +49 (0)7131 / 617-224  
info@beyerdynamic.de · www.beyerdynamic.de

### United States

beyerdynamic Inc. USA  
56 Central Ave. · Farmingdale, NY 11735  
Tel. +1 (631) 293-3200 · Fax +1 (631) 293-3288  
salesUSA@beyerdynamic.com · www.beyerdynamic.com

### Great Britain

beyerdynamic U.K. Ltd.  
17 Albert Drive · Burgess Hill RH15 9TN  
Tel. +44 (0)1444 / 258258 · Fax +44 (0)1444 / 258444  
sales@beyerdynamic.co.uk · www.beyerdynamic.co.uk

